

Differential / Dual-Channel WideBand Amplifier

MODEL 9250



- Large signal bandwidth to 15 MHz
- Small signal bandwidth to 30 MHz
- High amplitude to 40Vp-p (into high impedance)
- Slew rate to 200V/ μ s
- Low distortion
- Custom Configuration of:
 - Gain
 - Input impedance
 - Output impedance
 - Output configuration

The 9250 is a bench-top, 2U, half 19" rack size, fully metal case dual channel amplifier. The instrument can be configured to be used as two, single-ended independent channels, or as a one input with two differential outputs.

Input Characteristics

The inputs to the amplifiers be configured to match different source impedances such as 50 Ω , 75 Ω , or 1M Ω and the outputs can be configured to match different load impedances such as 50 Ω , 75 Ω , or 600 Ω . There are three inputs for each channel:

1. Main input. This input is located on the front panel is normally be used for signal inputs.
2. Auxiliary input. This input is located on the rear panel and can be used as a summing input.
3. DC Offset input. This input is also located on the rear panel and can be used for offsetting the signal level within the specified output level window.

Output Characteristics

The outputs are located on the front panel. There are two outputs, one for each channel. When the 9250 is configured as two separate amplifiers, the outputs generate amplified signals within the range of 40Vp-p into open circuit or 20Vp-p into matching load impedance. The bandwidth of the outputs is around 20MHz for large signals. Small signal bandwidth can reach 50MHz.

Instrument Configuration

The 9250 can be configured as a differential amplifier. In this case, the channel 2 input is disabled and channel 1 input is amplified and distributed differentially to both outputs. In this case, channel 1 output generates in-phase signal while channel 2 outputs an inverted signal that has exactly 180 phase offset to the normal output. Full amplitude and bandwidth is preserved when the 9250 operates in differential mode. The output impedance of the differential outputs is modified to 25 Ω , 37.5 Ω , or 300 Ω for differential drive of 50 Ω , 75 Ω , or 600 Ω loads. Using the differential mode, the 9250 does not sacrifice accuracy, nor does it sacrifice bandwidth.

Auxiliaries

The 9250 has two additional inputs for each channel allowing summation of two signals and providing an external control of DC level offset. These inputs are accessible from the rear panel only.

Target Applications

The amplifier case was designed to stack on top or below other Tabor products. It also can be mounted alongside a Tabor generator in a standard 19" rack. The waveform-amplifier combo is an ideal solution for virtually any high-voltage, wide bandwidth application.



TABOR ELECTRONICS Ltd.

Differential / Dual-Channel WideBand Amplifier

Model 9250



Service and Support

Beyond providing precision Test & Measurement instruments, Tabor Electronics provides unparalleled service and support, and is continuously finding new ways to bring added value to its customers.

Our after-sales services are comprehensive. They include all types of repair and calibration, and a single point of contact that you can turn to whenever you need assistance. As part of our extensive support, we offer individualized, personal attention Help Desk, both online and offline, via e-mail, phone or fax.

Tabor Electronics maintains a complete repair and calibration lab as well as a standards laboratory in Israel and USA. Service is also available at regional authorized repair/calibration facilities.

Contact Tabor Electronics for the address of service facilities nearest you.

Applications

For expert technical assistance with your specific needs and objectives, contact your local sales representative or our in-house applications engineers.

Manuals, Drivers, and Software Support

Every instrument comes equipped with a dedicated manual, developer libraries, IVI drivers, and software. However, if your specific manual is lost or outdated, Tabor Electronics makes it possible to log-on to its Download Center and get the latest data "in a click".

Product Demonstrations

If your application requires that you evaluate an instrument before you purchase it, a hands-on demonstration can be arranged by contacting your local Tabor Electronics representative or the Sales Department at our Corporate Headquarters.

Three-year Warranty

Every Tabor Electronics instrument comes with a three-year warrantee. Each one has full test results, calibration certificate, and CD containing product's manual and complete software package. Our obligation under this warranty is to repair or replace any instrument or part thereof which, within three years after shipment, proves defective upon examination. To exercise this warranty, write or call your local Tabor representative, or contact Tabor Headquarters and you will be given prompt assistance and shipping instructions.

CORPORATE HEADQUARTERS

9 Hattiasia St. P.O.Box404,
Tel Hanan, Israel 20302
☎ +972 (4) 8213393
☎ +972 (4) 8213388
www.taborelec.com

EUROPE

Austria
UEI-Viena
☎ +43 15451 588
☎ +43 15451 464

Benelux (Belgium, The Netherlands and Luxembourg)
BFI Optilas B.V.
☎ +31 172 44 60 60
☎ +31 172 44 34 14

Bulgaria
New-Tek Ltd.
☎ +359 296 25286
☎ +359 268 7110

Cyprus
Sprel Ltd.
☎ +357 2237 7159
☎ +357 2237 7284

Czech Republic & Slovakia
Testovací Technika s.r.o.
☎ +420 2 7478 2237
☎ +420 2 7478 1285

Denmark
Atimco AS
☎ +45 8625 8899
☎ +45 8625 5889

Finland
Tecono T&M Oy
☎ +358 9 2532 0000
☎ +358 9 2532 0022

France
Racal Instruments SAS
☎ +33 1 3923 2205
☎ +33 1 3923 2225

Germany
CompuMess Elektronik GmbH
☎ +49 89 321501-0
☎ +49 89 321501-11

Greece
American Technical Enterprises S.A.
☎ +30 210 5240 740
☎ +30 210 5249 995

Hungary
ProMet Merestechnika
☎ +36 24 521 240
☎ +36 24 521 253

Iceland
Rafor EHF
☎ +354 552 3424
☎ +354 552 8595

Italy
LP Instruments srl
☎ +39 2 4840 1713
☎ +39 2 4840 1852

Malta
Euch Zammit and Co. Ltd.
☎ +356 2149 8568
☎ +356 2148 0150

Norway
Nortelco AS
☎ +47 2257 6100
☎ +47 2257 6130

Poland
Helmar
☎ +48 22 436 3106
☎ +48 22 436 3110

Romania
InterNET SRL
☎ +40 21 312 1662
☎ +40 21 312 1663

Russia
CDIP
☎ +7 0959 56 2022
☎ +7 0959 56 2022

Spain & Portugal
Instrumentos De Media SL
☎ +34 91 300 0191
☎ +34 91 388 5433

Sweden
Ferner Elektronik AB
☎ +46 8 760 8360
☎ +46 8 760 8341

Switzerland
Elstar Elektronik AG
☎ +41 56 427 1888
☎ +41 56 427 1976

United Kingdom & Ireland
SEMATRON UK Ltd.
☎ +44 1256 812222
☎ +44 1256 812666

Yugoslavia (Bosnia, Croatia, Macedonia, Montenegro, Serbia, Slovenia)
Mechanic & Electronic Measurement
☎ +43 1943 4254
☎ +43 1943 4251

ASIA PACIFIC & JAPAN
Australia
Scientific Devices (Au) Pty Ltd.
☎ +61 3 9569 1366
☎ +61 3 9563 4728

India
AIMIL Ltd.
☎ +91 11 2695 0001
☎ +91 11 2695 0011

Japan
TOYO Corporation
☎ +81 3 3279 0771
☎ +81 3 3246 0645

Korea
ITB Corporation
☎ +82 2 549 8501
☎ +82 2 549 8502

New Zealand
Electrotest Ltd.
☎ +64 9 448 2600
☎ +64 9 448 2611

Philippines
Sunley Inc.
☎ +63 2751 1216
☎ +63 2815 0730

Singapore, Thailand & Vietnam
Gold Lite Engineering Pte Ltd.
☎ +65 6273 0487
☎ +65 6273 5006

Taiwan, China & Hong Kong
Precision International Corp.
Taiwan
☎ +886 2 85124888
☎ +886 2 85124900

China & Hong Kong
☎ +86 21 64401300
☎ +86 21 64400524

AFRICA
South Africa
Channels Measurement
☎ +27 11 254 8362
☎ +27 11 254 8451

MIDDLE EAST

Israel
Dan-El Technologies Ltd.
☎ +972 3 9271888
☎ +972 3 9271666

Turkey
Alfatek Test & Automation Ltd.
☎ +90 216 474 7355
☎ +90 216 474 7357

UNITED STATES US SALES & SUPPORT OFFICE
☎ +1 909 7970484
☎ +1 909 7974955

IL, IN, IA, KS, KY, MN, MO, NE, ND, SD, WI
Base Eight, Inc.
☎ +1 847 670 1680
☎ +1 847 670 1737

AZ, CO, ID, MT, NM, TX, EI Paso, UT, WY
Berry Technical Sales Inc.
☎ +1 303 665 9116
☎ +1 303 833 1294

AR, LA, OK, TX
Data Marketing Associates Inc.
☎ +1-972 661 0300
☎ +1 972 490 0836

OH, WV, PA, MI
Dytec EAST
☎ +1-330 405 8311
☎ +1 330 405 8313

DC, MD, VA
Eastern Instrumentation Corp.
☎ +1 410 884 7303
☎ +1 410 884 7306

PA, NJ
El Philly
☎ +1 856 231 0668
☎ +1 856 231 9022

HAW, NV, CA
Sierra Technical Sales
☎ +1 510 713 9957
☎ +1 510 713 9958

NJ, NY
Tera Technologies Inc.
☎ +1 888 921-TERA
☎ +1 888 449 2799

CT, ME, MA, NH, RI, VT
Test-Rep Associates, Inc.
☎ +1 978 692 8000
☎ +1 407 839 0337

AL, FL, GA, MS, NC, SC, TN
W.A Brown Instruments
☎ +1 407 648 9660
☎ +1 407 839 0337

CA, NV
W5 Inc.
☎ +1 949 212 1199
☎ +1 714 281 0767

CANADA
Testforce Systems Inc.
☎ +1 514 856 0970
☎ +1 514 856 6983



TABOR ELECTRONICS Ltd.

Specification Differential / Dual-Channel WideBand Amplifier

Model 9250



INPUT CHARACTERISTICS

Number of channels:	2 with single-ended outputs; 1 with differential outputs
Connector:	BNC
Impedance:	50Ω, 75Ω or 1MΩ
Coupling:	DC or AC
Damage Level:	12Vp-p (-6V to +6V peaks)
Frequency Range: (full power bandwidth)	DC to 15MHz DC coupled, 50Ω input/output impedance; 40kHz to 15MHz AC coupled, 50Ω/75Ω input impedance; 20Hz to 15MHz AC coupled, 1MΩ input impedance;

OUTPUT CHARACTERISTICS

Specification is given for the standard configuration only

GENERAL

Connector:	BNC
Impedance:	Single-Ended 50Ω, 75Ω, or 600Ω Differential 600Ω
Coupling:	DC or AC
Protection:	Short-circuit, 10 seconds
Gain:	x10, fixed (can be ordered from factory with different gain setting. Bandwidth may change with different gain configuration)
Polarity:	Output normal
Amplitude:	0 to 20Vp-p into matching impedance (50Ω, 75Ω, or 600Ω); 0 to 40Vp-p into high impedance

SINE WAVE CHARACTERISTICS

Small Signal:	Bandwidth 30MHz, at 2Vp-p (-3dB)
Accuracy:	±(3% of full-scale amplitude range + 25mV), Square wave at 1KHz
Flatness (10Vp-p):	±5% of amplitude to 1MHz; ±10% of amplitude to 15MHz
THD:	0.1%, 10Hz to 100kHz
Harmonics:	<-50dBc, 100kHz to 5MHz <-40dBc, 5MHz to 15MHz (10Vp-p)

SQUARE WAVE CHARACTERISTICS

Transition Time:	<22ns
Aberrations:	<7%

ENVIRONMENTAL

Operating Temperature:	0 - 50°C
Humidity:	RH 80% (non-condensing)
Storage Temperature:	-30°C - 80°C

GENERAL

Physical Size:	2U, half-rack size
Power Requirements:	85V to 265V, 47-63Hz, <25W
Dimensions:	3.5" x 8.3" x 15.4" (HxWxL)
Weight:	Approximately 7Lbs
Signal Ground:	Grounded to case ground
EMC Certification:	CE marked
Reliability:	MTBF per MIL-HDBK- 217E, 25°C, Ground Benign Designed to meet IEC EN61010-1, UL 3111-1
Safety:	
Workmanship Std:	Conform to IPC-A-610D
Supplied Accessories:	Power Cord, CD containing Operating Manual
Warranty:	3 years standard

ORDERING INFORMATION

Dual-Channel / Differential WideBand Amplifier,

MODEL	9250-10-50-50-D-S ⁽¹⁾
Gain:	10, 15 or 20, fixed ⁽²⁾
Input Impedance:	50 = 50Ω 75 = 75Ω 1M = 1MΩ
Output Impedance:	50 = 50Ω 75 = 75Ω 600 = 600Ω
Coupling:	D = DC A = AC
Output Configuration:	S = Two separated channels D = Single channel with differential outputs ⁽³⁾

⁽¹⁾ Standard Configuration

⁽²⁾ Custom gain from x10 to x20 can be ordered however, bandwidth may change.

⁽³⁾ Output impedance for differential drive is 600Ω only .



TABOR ELECTRONICS Ltd.